

KO8R715KIT DIESEL PUMP SETS



MACHINE DETAILS & PERFORMANCE DATA





PERKINS ON TROLLEY WITH ROVATTI PUMP





STANDARD EQUIPMENT

- 4 cylinder air-cooled engine, complete with engine liquids and fuel tank.
- Rovatti F43K80/4H Pump.
- Mounted on two pneumatic wheels trolley, with 60 built in tank.
- Flanged Centrifugal PUMP.
- Electric start with key block and battery.
- PERKINS: ELCOS CEM 250/00 control panel with electric system, engine control device, pressure gauge, pressure switch, 24 hour timer.
- Battery.
- ABS Roof.
- Engine running indicator light.
- Work light for around unit.

Machine Options	Code					
Priming System Kirpy	406053					
Electric Priming Pump	EPP					

Computer Options	Code
Upgrade to Elcos CIM 131	CIM131UPGRADE
Upgrade to Elcos CIM 137	CIM137UPGRADE





WEIGHTS AND DIMENSIONS

SIZE (cm)												
Α	A c	Вс	C c	Dc	E c	F	G c	Н	I	N	P	Q c
315.0	181.0	122.9	193.7	174.2	28.0	137.0	174.0	130.0	100.0	128.0	40.0	222.0

 $^{^{\}ast}\,$ Please note dimensions are to be used as a guide only.








JOHN DEERE ENGINE WITH CAPRARI PUMP

ROVATTI PUMP F43K80/4H

PUMP PERFORMANCE RANGE









JOHN DEERE ENGINE WITH CAPRARI PUMP

ROVATTI PUMP F43K80/4H

GENERAL PUMP DATA

DNa	ers ation	l/s	0	8.3	10	11.7	13.3	15	16.7	18.3	20	21.7	23.3	25
DNm	npeller nbinat	m ³ /h	0	30	36	42	48	54	60	66	72	78	84	90
mm	O -	l/min	0	500	600	700	800	900	1000	1100	1200	1300	1400	1500

Capacity at 1450 N [min-1]

00 v 4	- ,,	m	58.5	55	52.2	49	44.7	39.7	33.6	27	19.3	
80 x 6	5 H	KW	4.1	7.2	7.2	8.2	8.6	9	9.3	9.6	9.7	
	NPSH n	n	_	2.5	2.6	2.7	2.9	3.1	3.5	4.2	5.0	

Capacity at 1800 N [min-1]

00 v 4F	Н	m	90.8	87	85	82	78	73.6	68	61.3	54	46
80 x 65		KW	7.7	12.3	13.3	14.2	15.1	1.8	16.6	17.2	17.8	18.2
1	NPSH m	1	-	2.5	2.55	2.65	2.75	2.9	3.2	3.55	4.05	4.65

Capacity at 2000 N [min-1]

90 v 45	Н	m	111.3	108	106	103	100	95.5	90.3	84	77	69.5	61
80 x 65	П	KW	8.9	16	17.2	18.4	19.7	20.6	21.6	22.6	23.4	23.9	24.3
١	IPSH m		_	2.5	2.55	2.65	2.75	2.85	3.1	3.4	3.7	4.15	4.7

Capacity at 2300 N [min-1]

80 x 65 H	ы	m	146.8	44	143	141	138	134	129	123	116	109	101	93
80 X 05	П	kW	14.8	23.6	25.2	26.9	28.5	30	31.5	32.8	34.1	35.2	36.1	36.8
N	PSH m		-	2.5	2.5	2.55	2.6	2.8	3	3.2	3.5	3.9	4.3	4.9







JOHN DEERE ENGINE WITH CAPRARI PUMP

PERKINS MOTORS 404D-22 IOPU

GENERAL ENGINE DATA

ļ	Intermittent -	Rated	power/	'Rated	speed

Intermittent - Peak torque

Intermittent - Torque rise

ENGINE PERFORMANCE RANGE

404D-22 IOPU

