

IRRIGATION VALVES





Phone: 07 3624 0300 Email: sales@rodneyind.com.au Web: www.rodneyind.com.au



FOR RANGE AND RELIABILITY, CHOOSE RODNEY INDUSTRIES

With a range that expands over 100 valve types and sizes, you are sure to find the Valve to suit your requirements. If you don't ... we can make it!

- Made in Queensland.
- Large range of Valves available in sizes to suit your requirements.
- For use in a wide range of applications, including: ocean outlets, transfer ponds, channels.
- · Hot dipped galvanized.
- · Spare parts readily available.








Gibault Joints enable the repair of pipes and pipeline components and fittings in the field. They are often used on the outlet end of the Eco Check Valve.

Our range of Gibault Joints are available in 300mm right through to 1500mm.



ECO CHECK VALVES



WITH BYPASS

We offer the strongest and most efficient Eco-Check Valve in the rural market. Fully galvanized and available in 3" right through to a massive 36". For sizes 14" to 36" a maintenance hatch is standard.

SIZES AVAILABLE:

80mm (3") through to 900mm (36")

ABILITY TO BE MODIFIED?:

Customer is able to purchase a standard Eco Check Valve or with a bypass. We also offer the option of certain sizes with a maintenance hatch or with a bypass.

Flange type can be changed if necessary.

CHECK VALVES





WITH BYPASS

Commonly used on the discharge of a pump to stop flow back to the pump and to regulate flow to irrigation.

Our range Check Valves are available on 80mm (3") through to 750mm (30") and are available both standard or with bypass.

SIZES AVAILABLE:

80mm (3") through to 750mm (30")

ABILITY TO BE MODIFIED?:

Customer is able to purchase a standard Check Valve or with a bypass.

Flange type can be changed if necessary.

FLAP VALVES





HEAVY DUTY

For use in a wide range of applications, including ocean outlets and transfer ponds. Flap Valve range available is flanged or with spigots to suit grout-in or rubber ring joint applications.

SIZES AVAILABLE:

Standard: 350mm (14") through to 900mm (36") Heavy Duty: 80mm (3") through to 750mm (30")

ABILITY TO BE MODIFIED?:

Customer is able to purchase a standard Flap Valve or Heavy Duty.

Flange type can be changed if necessary.

GATE CHECK VALVES





WITH BYPASS

Commonly used on the discharge of a pump to stop flow back to the pump and to regulate flow to irrigation.

Our range Check Valves are available on 80mm (3") through to 750mm (30") and are available both standard or with bypass.

SIZES AVAILABLE:

80mm (3") through to 900mm (36")

ABILITY TO BE MODIFIED?:

Customer is able to purchase a standard Eco Check Valve or with a bypass. We also offer the option of certain sizes with a maintenance hatch or with a bypass.

Flange type can be changed if necessary.

THE 'FAB' ONES

You cannot be in the industry for over 45 years and not understand the importance of quality, durability and performance your products have for your customers. This is not only true for our standard stock irrigation valves, but also for all our fabricated products.

If you have a project that requires a valve out of the ordinary, look no further than Rodney Industries. With our Sales and Design team, we are sure to find the solution you are looking for.





